

Adding Freshness into your recipes!



Middleby Celfrost brings to India, a truly world class range of Gastronorm refrigeration products, that enhance the skills of modern kitchen professionals. With Celfrost Professional, you say good-bye to power-guzzling, rust-catching and crudely fabricated refrigeration systems and actually enjoy the benefits of sturdy equipment built with AISI 304 Grade Stainless Steel; flawless European controls; reliable European refrigeration system, energy saving design and dependable after sales service support.



Refrigerated Reach in Cabinets

Celfrost Professional Reach In Cabinets suitable for 2 x GN 1/1 sizes are built in SS304 with reliable Danfoss / Aspera compressors, LED temperature display, rounded internal edges for complete hygiene, removable magnetic gaskets for ease of cleaning, self closing doors with heaters to prevent condensation and heavy duty lockable castors. Available in Chillers or Deep Freezers with two or four door options; a choice of Static or Ventilated refrigeration; and in 600 & 1200ltr. capacities.



GN 650 TNM (New)
GN 650 BTM (New)
GN 600 TNM / GN 600 BTM



GN 1410 TNM (New)
GN 1410 BTM (New)
GN 1200 TNM / GN 1200 BTM

Undercounters

While retaining the basic features of the Reach in Cabinets mentioned above, these refrigerated work tables, mounted on heavy duty lockable castors, combine storage and preparation thereby enhancing the effectiveness of kitchen professionals and are suitable for GN 1/1 sizes. Chillers or Deep Freezers available in 2 and 3 door options.



GN 2100 TN
GN 2100 BT



GN 3100 TN
GN 3100 BT

Prep Counters

Celfrost Professional Prep Counters bring in a unique experience in the preparation of pizzas, salads, starters, sandwiches, desserts and more. Mounted on heavy duty lockable castors and available in 2 and 3, self closing door variants.



SH 2000 / 800



SH 3000 / 800

Saladettes & Countertop Displays

The Saladettes come with a refrigerated display top that can take in frozen yogurt toppings, salads etc. in 10 x GN ¼ pans (not included). It also has a night cover. A two door refrigerated section underneath is handy to store additional foodstuff. The Countertop display comes with a glass sneeze guard; is equipped with its own refrigeration unit and accepts 5 GN ¼ pans (not included).



VRX 1200/330

Gastronorm (GN) Dimensions : L x W

GN 1/1	>	530 mm x 327 mm
GN 1/2	>	327 mm x 265 mm
GN 1/3	>	327 mm x 176 mm
GN 2/3	>	354 mm x 325 mm
GN 1/4	>	265 mm x 163 mm
GN 1/6	>	176 mm x 163 mm

Depth in case of pans can vary from 65, 100 or 150 mm



S 900

Blast Chillers & Shock Freezers

The powerful Celfrost Professional Blast Chillers / Freezers are most ideal for reducing the temperature of cooked food from 90 °C to +3 °C or -18°C rapidly, thereby rendering it safe from bacterial growth and fit for ensuing storage and consumption later on. Available in 4 capacities, they are suitable for both GN 1/1 and 400x600 mm tray sizes.



D3



D5



D10



D14

Technical Specifications

Product	Model	Dimension (WxDxH) mm	Volume (in ltrs.)	Design (GN Compatibility)	Net Weight (in kgs)	No. of Doors	No. of shelves	Temperature Range (°C)	Input Power (in watts)	Refrigerant
Reach-in Refrigerators (Ventilated Cooling)	GN 650 TNM (New)	680 x 800 x 2010	600	2 x GN 1/1	115	2	3	2 to 8°C*	350	R134a
	GN 1410 TNM (New)	1340 x 800 x 2010	1200	2 x GN 1/1	144	4	6	2 to 8°C*	800	R134a
Reach-in Refrigerators (Static Cooling)	GN 600 TNM	680 x 810 x 2000	600	2 x GN 1/1	145	2	3	2 to 8°C*	300	R134a
	GN 1200 TNM	1340 x 810 x 2000	1200	2 x GN 1/1	195	4	6	2 to 8°C*	600	R134a
Reach-in Freezers (Ventilated Cooling)	GN 650 BTM (New)	680 x 800 x 2010	600	2 x GN 1/1	124	2	3	-18 to -22°C*	750	R404a
	GN 1410 BTM (New)	1340 x 800 x 2010	1200	2 x GN 1/1	182	4	6	-18 to -22°C*	1000	R404a
Reach-in Freezer (Static Cooling)	GN 600 BTM	680 x 810 x 2000	600	2 x GN 1/1	145	2	3	-10 to -20°C*	600	R404a
	GN 1200 BTM	1340 x 810 x 2000	1200	2 x GN 1/1	195	4	6	-10 to -20°C*	700	R404a
Undercounter Chillers (Ventilated Cooling)	GN 2100 TN	1360 x 700 x 860	282	1 x GN 1/1	98	2	2	2 to 8°C*	235	R134a
	GN 3100 TN	1795 x 700 x 860	417	1 x GN 1/1	134	3	3	2 to 8°C*	235	R134a
Undercounter Freezers (Ventilated Cooling)	GN 2100 TN	1360 x 700 x 860	282	1 x GN 1/1	140	2	2	-10 to -20°C*	955	R404a
	GN 3100 TN	1795 x 700 x 860	417	1 x GN 1/1	150	3	3	-10 to -20°C*	955	R404a
Prep Counters (Ventilated Cooling)	SH 2000/800	1510 x 800 x 1050	337	6 x GN 1/3	155	2	2	2 to 8°C**	335	R134a
	SH 3000/800	2020 x 800 x 1050	497	10 x GN 1/4	164	3	3	2 to 8°C**	495	R134a
Saladettes (Static Cooling)	S 900	900 x 700 x 850	-	10 x GN 1/4	70	2	2	2 to 8°C**	245	R134a
Counter Top Displays (Static Cooling)	VRX 1200/330	1200 x 335 x 225**	-	5 x GN 1/4	25	-	-	2 to 8°C**	209	R134a

Product	Model	Exterior Dimension (WxDxH) mm	Internal Dimension (WxDxH) mm	Pan Support (GN 1/1)	Pan Support (400 x 600 mm)	Net Weight (in kgs)	Power Supply	Refrigerant	Temperature Drop (°C)	Input Power (in watts)	Mode of Refrigeration
Blast Chillers/Freezers	D3	800 x 815 x 945	660 x 640 x 330	3 Sets	3 Sets	80	230V/50Hz	R404a	90°C to 3°C in 90 minutes	703	Ventilated
	D5	800 x 815 x 1015	660 x 640 x 400	5 Sets	5 Sets	95	230V/50Hz	R404a		801	Ventilated
	D10	800 x 815 x 1645	660 x 640 x 870	10 Sets	10 Sets	150	230V/50Hz	R404a	90°C to -18°C in 240 minutes	1298	Ventilated
	D14	800 x 815 x 2117	660 x 640 x 1170	14 Sets	14 Sets	210	380V/50Hz/3Ph	R404a		2000	Ventilated

* Tested to perform under ambient temperature of 43°C

** Tested to perform under ambient temperature of 32°C

With a view to ensure ongoing product enhancement/development, Middleby Celfrost reserves the right to change any specification, without prior notice.

ISO9001:2000



RoHS

MIDDLEBY CELFROST

Our Valuable Customers:



Ahmedabad Showroom : 9, Dev Complex, Under GIPS Hospital, Parimal Cross Roads, Ellisbridge, A`bad-6
079-4006 0525, Email : ramdevgroup@hotmail.com

Surat Showroom : 841/B, Jamna Niwas, Opp Guj Samachar, Udhana Darwaja, Ring Rd, Surat-2
9099915535 Email : ramdevref@gmail.com

Service : Ahmedabad- 079-6545 5943, 94267 43229 Surat: 0261-263 1631, 98255 11027

Quick Contact:

